



WAGO T-DISTRIBUTION CONNECTOR; 2-POLE; 1 INPUT; 2 OUTPUTS; GREEN

Note on Contact Resistance: $\approx 3m\Omega$ contact resistance

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 50; V

Tensiune nominala de supratensiune (III/3): 0,8; kV

Curent nominal: 3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Numar poli: 2;

Total number of potentials: 2;

Latime: 15 mm / 0.591 inch;

Inaltime: 28,9 mm / 1.138 inch;

Adancime: 28,7 mm / 1.13 inch;

Technologie: KNX;

Coding: F;

Mating force of a plug-in connection: approx. 10 ... 15 N;

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ≈ 200 ;

Distributor type: T-distribution connector;

Marking: 1+ 2-;

Protection type: IP20;

Note on protection type: Only when mated and secured with a strain relief housing (These compact connectors are not designed for use in open, easily accessible areas.);

Potential marking: 1+ 2-;

Application: KNX;

Tip contact (pluggable connector): Socket/plug;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Locking lever: yes;
Culoare: green;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper alloy (surface-treated);
Greutate: 12,6; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454547684;
Customs tariff number: 85366990990;
Pret: 61,45 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/t-distribution-connector-2-pole-1-input-2-outputs-green-131243>