



**WAGO DOUBLE-DECK TERMINAL BLOCK; THROUGH/THROUGH TERMINAL BLOCK; WITH END PLATE; N/N; WITH MARKER CARRIER; SUITABLE FOR EX I APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 2,50 MM<sup>2</sup>; BLUE**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 15; A

Tensiune nominala UL (Use Group D): 600; V

Curent nominal UL (Use Group D): 5; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Number of connection points (connection type): 2;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Number of connection points: 2;  
Numar total de conexiuni: 4;  
Total number of potentials: 2;  
Numar nivele: 2;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Latime: 6,2 mm / 0.244 inch;  
Inaltime from upper-edge of DIN-rail: 61,8 mm / 2.433 inch;  
Adancime: 69,7 mm / 2.744 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Potential marking: N/N;  
Marking level: Center/side marking;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,31; MJ  
Greutate: 13,7; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821299080;  
Customs tariff number: 85369010000;  
Pret: 15,11 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-deck-terminal-block-through-through-terminal-block-with-end-plate-n-n-with-marker-carrier-suitable-for-ex-i-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-blue-131315>