



**WAGO 1-CONDUCTOR/1-PIN DOUBLE DECK RECEPTACLE TERMINAL BLOCK;
GROUND CONDUCTOR/THROUGH TERMINAL BLOCK; PE/L; WITH MARKER
CARRIER; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®;
2,50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 690; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Curent nominal 2: 28; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 5,2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 61,4 mm / 2.417 inch;

Adancime: 80,1 mm / 3.154 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Potential marking: PE/L;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,259; MJ

Greutate: 15,1; g

Product Group: 18 (X-COM-System);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454994792;

Customs tariff number: 85369010000;

Pret: 24,07 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-1-pin-double-deck-receptacle-terminal-block-ground-conductor-through-terminal-block-pe-l-with-marker-carrier-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-131531>