



**WAGO 1-CONDUCTOR FEMALE PLUG; 100% PROTECTED AGAINST MISMATING;
GRIPPING PLATE; 10 MM²; PIN SPACING 7.62 MM; 3-POLE; 10,00 MM²; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Tensiune nominala (III/2): 1000; V

Tensiune nominala de supratensiune (III/2): 8; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 8; kV

Curent nominal: 41; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 42; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 41; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 6 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0.5 ... 6 mm²;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar poli: 3;

Numar total de conexiuni: 3;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanța între pini: 7.62 mm / 0.3 inch;
Lățime: 24.74 mm / 0.974 inch;
Înălțime: 27.5 mm / 1.083 inch;
Adâncime: 41.9 mm / 1.65 inch;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductors;
Mismatching protection: Yes;
Culoare: light gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Material of the additional spring for socket contact: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 23,9; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143511223;
Customs tariff number: 85366990990;
Pret: 31,47 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-female-plug-100-protected-against-mismatching-gripping-plate-10-mm2-pin-spacing-7-62-mm-3-pole-10-00-mm2-light-gray-131598>