



**WAGO DOUBLE-DECK TERMINAL BLOCK; 4-CONDUCTOR GROUND TERMINAL BLOCK; PE; WITH END PLATE; WITH MARKER CARRIER; INTERNAL COMMONING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 1 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 1,00 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1 mm<sup>2</sup>;

Solid conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Solid conductor; push-in termination: 0.5 ... 1.5 mm<sup>2</sup> / 20 ... 16 AWG;

Fine-stranded conductor: 0.14 ... 1.5 mm<sup>2</sup> / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0.5 ... 0.75 mm<sup>2</sup> / 20 ... 18 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 4.2 mm / 0.165 inch;

Inaltime from upper-edge of DIN-rail: 61.8 mm / 2.433 inch;

Adancime: 69.7 mm / 2.744 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Potential marking: PE;

Marking level: Center/side marking;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,219; MJ  
Greutate: 12,1; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821037699;  
Customs tariff number: 85369010000;  
Pret: 32,13 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/double-deck-terminal-block-4-conductor-ground-terminal-block-pe-with-end-plate-with-marker-carrier-internal-commoning-for-din-rail-35-x-15-and-35-x-7-5-1-mm2-push-in-cage-clamp-1-00-mm2-green-yellow-131623>