



**WAGO TRIPLE-DECK TERMINAL BLOCK; GROUND
CONDUCTOR/THROUGH/THROUGH TERMINAL BLOCK; PE/L/L; SUITABLE FOR
EX E II APPLICATIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; CAGE
CLAMP®; 2,50 MM²; LIGHT GRAY**

Ratings per: IEC/EN 60947-7-1;
Current nominal: 24; A
Nominal voltage EN (Ex e II): 440; V
Connection technology: CAGE CLAMP®;
Operating tool:
Connectable conductor materials: Copper;
Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;
Total number of connections: 6;
Total number of potentials: 3;
Number of levels: 3;
Wiring type: Front-entry wiring;
Width: 5 mm / 0.197 inch;
Height from upper edge of DIN-rail: 52.5 mm / 2.067 inch;
Length: 106 mm / 4.173 inch;
Design: horizontal;
Mounting: DIN-35 rail;
Potential marking: PE/L/L;
Marking level: Side marking;
Color: light gray;
Weight: 21,3; g
Packaging: BOX;

Tara de origine: DE;
GTIN: 4045454323691;
Customs tariff number: 85369010000;
Pret: 36,13 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/triple-deck-terminal-block-ground-conductor-through-through-terminal-block-pe-l-l-suitable-for-ex-e-ii-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-light-gray-131736>