





WAGO T-DISTRIBUTION CONNECTOR; 3-POLE; COD. R; 1 INPUT; 2 OUTPUTS; 3 LOCKING LEVERS; FOR FLYING LEADS; ORANGE

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tesiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 25; A Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 23; A Numar poli: 3; Total number of potentials: 3; Distanta intre pini: 10 mm / 0.394 inch; Latime: 34 mm / 1.339 inch; Inaltime: 36,1 mm / 1.421 inch; Adancime: 48,9 mm / 1.925 inch; Coding: R; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: When locked: > 80 N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: ?200, without resistive load 100, with resistive load IN = 25 A, tested (4) mm²/AWG 12); Distributor type: T-distribution connector; Marking: LON LON S; Protection type: IP20; Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Potential marking: LON LON S; Application: LON Bus; Suitable: for flying leads; Tip contact (pluggable connector): Socket/plug; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: yes; Culoare: orange; Material izolator: Polyamide 66 (PA 66); Contact material: Copper or copper alloy (surface-treated); Fire load: 0,248; MJ Greutate: 13,7; g Processing temperature: $-5 \dots +40 \,^{\circ}C$; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C; Product Group: 20 (WINSTA); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454186371; Customs tariff number: 85366990990; Pret: 25,92 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/t-distribution-connector-3-pole-cod-r-1-input-2-outputs-3-locking-levers-for-flying-leads-orange-131791