



WAGO 4-CONDUCTOR TERMINAL STRIP; 12-POLE; ON BOTH SIDES WITH PUSH-BUTTONS; WITH SNAP-IN MOUNTING FEET; FOR PLATE THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 MM Ø; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY

Tesiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool; Push-button;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 12;

Numar total de conexiuni: 48;

Total number of potentials: 12;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 124.4 mm / 4.898 inch;

Inaltime de la fata: 23.2 mm / 0.913 inch;

Adancime: 28 mm / 1.102 inch;

Module Latime: 10 mm / 0.394 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,97; MJ

Greutate: 55; g

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918628297;
Customs tariff number: 85369010000;
Pret: 59,42 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-terminal-strip-12-pole-on-both-sides-with-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-gray-131973>