



WAGO 4-CONDUCTOR/2-PIN DOUBLE-DECK CARRIER TERMINAL BLOCK; 4-CONDUCTOR/2-PIN THROUGH TERMINAL BLOCK; L/L; INTERNAL COMMONING; CONDUCTOR ENTRY WITH VIOLET MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 6;

Total number of potentials: 1;

Numar nivele: 2;

Wiring type: Front-/Side-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 39.8 mm / 1.567 inch;

Adancime: 91 mm / 3.583 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Potential marking: L;

Marking level: Side marking;

Culoare: gray;

Greutate: 13,8; g

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143614269;
Customs tariff number: 85366990990;
Pret: 20,36 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-2-pin-double-deck-carrier-terminal-block-4-conductor-2-pin-through-terminal-block-1-1-internal-commoning-conductor-entry-with-violet-marking-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-132215>