



**WAGO PANEL FEEDTHROUGH MALE CONNECTOR; CLAMPING COLLAR; PIN
SPACING 5 MM; 2-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Numar poli: 2;

Total number of potentials: 2;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 24.2 mm / 0.953 inch;

Inaltime: 14.4 mm / 0.567 inch;

Adancime: 33.4 mm / 1.315 inch;

Tip montaj: Mounting flange;

Tip montaj: Feed-through mounting; Panel mounting;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for pluggable connectors;

Mismating protection: No;
Locking of plug-in connection: Male locking latch;
Culoare: light gray;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,068; MJ
Greutate: 2,8; g
Temperatura lucru: -60 ... +100 °C;
Product Group: 26 (picoMAX);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821165705;
Customs tariff number: 85366990990;
Pret: 7,94 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/panel-feedthrough-male-connector-clamping-collar-pin-spacing-5-mm-2-pole-light-gray-132227>