



**WAGO PCB TERMINAL BLOCK; LEVER; 6 MM²; PIN SPACING 10 MM; 11-POLE;
CAGE CLAMP®; 6,00 MM²; GREEN-YELLOW, BLUE, GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Tensiune nominala (III/2): 1000; V

Tensiune nominala de supratensiune (III/2): 8; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 8; kV

Curent nominal: 41; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 30; A

Tensiune nominala UL (Use Group C): 150; V

Curent nominal UL (Use Group C): 30; A

Tensiune nominala UL (Use Group D): 600; V

Curent nominal UL (Use Group D): 5; A

Certificari: UL 1059;

Solid conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Fine-stranded conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Fine-stranded conductor; with insulated ferrule: 0,5 ... 6 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0,5 ... 6 mm²;

Conductor connection direction to PCB: 30; °

Numar poli: 11;

Inaltime de la fata: 25,5 mm / 1.004 inch;

Solder pin dimensions: 1 x 1,4 mm;

Diametrul de gaurire cu toleranta: 1,8 (+0,1) mm;

PCB contact: THT;

Solder pin arrangement: over the entire terminal strip (in-line);

Culoare: green-yellow, blue, gray;

Material izolator: Polyamide 66 (PA 66);

Flammability class per UL94: V0;

Contact material: Cupru electrolitic(ECu);

Greutate: 66,4; g

Tip ambalare: BOX;

Tara de origine: PL;

GTIN: 4055143927031;

Customs tariff number: 85369010000;

Pret: 76,92 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pcb-terminal-block-lever-6-mm2-pin-spacing-10-mm-11-pole-cage-clamp-6-00-mm2-green-yellow-blue-gray-132276>