



**WAGO 2-CONDUCTOR DISCONNECT TERMINAL BLOCK; WITH PIVOTING KNIFE
DISCONNECT; WITH TEST OPTION; ORANGE DISCONNECT LINK; FOR DIN-RAIL
35 X 15 AND 35 X 7.5; 6 MM²; PUSH-IN CAGE CLAMP®; 6,00 MM²; BLACK**

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 30; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 2,5 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 mm² / 16 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 7,5 mm / 0.295 inch;

Inaltime from upper-edge of DIN-rail: 36,8 mm / 1.449 inch;

Adancime: 96,3 mm / 3.791 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;
Culoare: black;
Material izolator: Polyamide 66 (PA 66);
Greutate: 18; g
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4055143674485;
Customs tariff number: 85365080900;
Pret: 27,95 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-disconnect-terminal-block-with-pivoting-knife-disconnect-with-test-option-orange-disconnect-link-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-push-in-cage-clamp-6-00-mm2-black-132345>