



**WAGO 1-CONDUCTOR/1-CONDUCTOR TERMINAL BLOCK FOR PLUGGABLE  
MODULES; 8-POLE; WITH 2-CONDUCTOR TERMINAL BLOCKS; WITH 2 JUMPER  
POSITIONS; WITH ORANGE SEPARATOR PLATE; FOR DIN-RAIL 35 X 15 AND 35 X  
7.5; 4 MM<sup>2</sup>; CAGE CLAMP®; 4,00 MM<sup>2</sup>; GRAY**

Tesiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm<sup>2</sup>;

Solid conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 8;

Numar total de conexiuni: 8;

Total number of potentials: 8;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 21.1 mm / 0.831 inch;

Inaltime from upper-edge of DIN-rail: 28.5 mm / 1.122 inch;

Adancime: 87.5 mm / 3.445 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,736; MJ  
Greutate: 37,5; g  
Product Group: 18 (X-COM-System);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918935272;  
Customs tariff number: 85369010000;  
Pret: 40,54 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-1-conductor-terminal-block-for-pluggable-modules-8-pole-with-2-conductor-terminal-blocks-with-2-jumper-positions-with-orange-separator-plate-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-132396>