



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-ENDED; 3-POLE;
COD. A; H05VV-F 3G 2.5 MM²; 1 M; 2,50 MM²; BLACK

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 20; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 23; A

Numar poli: 3;

Total number of potentials: 3;

Ground function: with preceding ground contact;

Conductor preparation: tip-bonded;

Sheathed cable diameter: 9,2 ... 11,4 mm;

Sectiunea transversala a firului: 2,5; mm²

Strip length (outer insulation): 55; mm

Connection type: Plug - Free end;

Distanta intre pini: 10 mm / 0.394 inch;

Total length: 1; m

Coding: A;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: when locked: > 80N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);

Connection type: Plug - Free end;

Type of pre-assembled cable: Connecting cable;

Cable type: H05VV-F 3G2.5;
Marking: L ? N;
Protection type: IP 2xD;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Potential marking: L ? N;
Application: General mains applications;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: black;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Fire load: 30,025; MJ
Connector Culoare: black;
Printing color of mating face: white;
Strain relief Culoare: black;
Printing color of strain relief: white;
Sheathed cable Culoare: black;
Printing color of sheathed cable: white;
Sheath material: PVC;
Greutate: 174,7; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: DE;
GTIN: 4055143492614;
Customs tariff number: 85444290900;
Pret: 35,53 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-3-pole-cod-a-h05vv-f-3g-2-5-mm2-1-m-2-50-mm2-black-132540>