



WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; SOCKET/PLUG; 2-POLE;
COD. F; 3 M; GRAY

Note on Contact Resistance: ?<p>approx. 3m? contact resistance</p>;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 50; V
Tensiune nominala de supratensiune (III/3): 0,8; kV
Curent nominal: 3; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Conductor diameter: 0,8 mm;
Numar poli: 2;
Total number of potentials: 2;
Conductor preparation: tip-bonded;
Connection type: Socket - Plug;
Total length: 3; m
Technologie: KNX;
Coding: F;
Mating force of a plug-in connection: approx. 10 ... 15 N;
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;
Number of mating cycles: ?200;
Connection type: Socket - Plug;
Type of pre-assembled cable: Interconnecting cable;
Cable type: J-Y(ST)Y...LG 1x2x0.8;
Marking: 1+ 2-;
Protection type: IP20;
Note on protection type: Only when mated and secured with a strain relief housing (These compact connectors are not designed for use in open, easily accessible areas.);
Potential marking: 1+ 2-;

Application: KNX;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Dca;
Contact material: Copper alloy (surface-treated);
Fire load: 3,462; MJ
Connector Culoare: light gray;
Strain relief Culoare: black;
Sheathed cable Culoare: gray;
Halogen-free: Yes;
Greutate: 115; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: PL;
GTIN: 4050821468226;
Customs tariff number: 85444290900;
Pret: 119,26 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-interconnecting-cable-socket-plug-2-pole-cod-f-3-m-gray-132551>