



**WAGO 2-PIN DISCONNECT CARRIER TERMINAL BLOCK; WITH SHIELD CONTACT;  
WITH 2 JUMPER POSITIONS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 4,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 28.5 mm / 1.122 inch;

Adancime: 101 mm / 3.976 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,177; MJ

Greutate: 11,4; g

Product Group: 18 (X-COM-System);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4044918630115;

Customs tariff number: 85365080900;

Pret: 14,39 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-pin-disconnect-carrier-terminal-block-with-shield-contact-with-2-jumper-positions-for-din-rail-35-x-15-and-35-x-7-5-4-00-mm2-gray-132663>