



### **WAGO CONDUCTOR SUPPORT; 3-POLE; 2,50 MM<sup>2</sup>; WHITE**

Tensiune nominala (III/2): 500; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Curent nominal: 16; A  
Curent nominal 2: 6; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;  
Numar poli: 3;  
Numar tipuri de conexiuni: 1;  
Latime: 39,1 mm / 1.539 inch;  
Inaltime de la fata: 19 mm / 0.748 inch;  
Culoare: white;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,111; MJ  
Greutate: 15,1; g  
Temperature stability: 105; °C  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4045454415440;  
Customs tariff number: 85369010000;  
Pret: 12,06 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/conductor-support-3-pole-2-50-mm2-white-132665>