



WAGO CONDUCTOR SUPPORT; 3-POLE; 2,50 MM²; WHITE

Tensiune nominala (III/2): 500; V

Tensiune nominala de supratensiune (III/2): 4; kV

Curent nominal: 16; A

Curent nominal 2: 6; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;

Numar poli: 3;

Numar tipuri de conexiuni: 1;

Latime: 39,1 mm / 1.539 inch;

Inaltime de la fata: 19 mm / 0.748 inch;

Culoare: white;

Material group: I;

Material izolator: Polyamide 66 (PA 66);

Flammability class per UL94: V0;

Clamping spring material: Chrome nickel spring steel (CrNi);

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;

Fire load: 0,111; MJ

Greutate: 15,1; g

Temperature stability: 105; °C

Tip ambalare: BOX;

Tara de origine: PL;

GTIN: 4045454415440;

Customs tariff number: 85369010000;

Pret: 12,06 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/conductor-support-3-pole-2-50-mm2-white-132665>