



**WAGO 3-CONDUCTOR FUSE TERMINAL BLOCK; WITHOUT BLOWN FUSE INDICATION; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 10,00 MM<sup>2</sup>; LIGHT GRAY**

Tensiune nominala (III/3): 800; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: Screw-clamp connection/Studs;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG;  
Strip length: 13 mm / 0.51 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 24 mm / 0.945 inch;  
Inaltime from upper-edge of DIN-rail: 73 mm / 2.874 inch;  
Adancime: 74 mm / 2.913 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Culoare: light gray;  
Greutate: 98,4; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: FR;  
GTIN: 4017332280501;  
Customs tariff number: 85369095990;  
Pret: 80,20 LEI (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/3-conductor-fuse-terminal-block-without-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-10-00-mm2-light-gray-132794>