



WAGO THR PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 3.5 MM; 7-POLE; PUSH-IN CAGE CLAMP®; 1,50 MM²; BLACK

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 200; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tensiune nominala (II/2): 320; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 8; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 8; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 5; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 10; A
Tensiune nominala CSA (Use Group D): 300; V
Curent nominal CSA (Use Group D): 10; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-button;
Solid conductor: 0,2 ... 1,5 mm² / 24 ... 16 AWG;
Fine-stranded conductor: 0,2 ... 1,5 mm² / 24 ... 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0,25 ... 1 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1 mm²;
Strip length: 8,5 ... 9,5 mm / 0.33 ... 0.37 inch;
Conductor connection direction to PCB: 45; °

Numar poli: 7;
Numar total de conexiuni: 7;
Total number of potentials: 7;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3,5 mm / 0.138 inch;
Latime: 26 mm / 1.024 inch;
Inaltime: 15,5 mm / 0.61 inch;
Inaltime de la fata: 13,1 mm / 0.516 inch;
Adancime: 12 mm / 0.472 inch;
Lungimea pinului de contact: 2,4; mm
Solder pin dimensions: 0,4 x 0,75 mm;
Diametru placat prin gaura (THR): 1 (+0,1) mm;
PCB contact: THR;
Solder pin arrangement: over the entire terminal strip (staggered);
Number of solder pins per potential: 1;
Culoare: black;
Material group: III a;
Material izolator: Polyamide 46 (PA 46);
Flammability class per UL94: V2;
Clamping spring material: Copper alloy;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 3,4; g
Temperatura lucru: -60 ... +115 °C;
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4055143243384;
Customs tariff number: 85369010000;
Pret: 9,26 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/thr-pcb-terminal-block-push-button-1-5-mm2-pin-spacing-3-5-mm-7-pole-push-in-cage-clamp-1-50-mm2-black-132812>