



**WAGO 2-CONDUCTOR COMBI STRIP; 100% PROTECTED AGAINST MISMATING;  
LOCKING LEVER; 1.5 MM<sup>2</sup>; PIN SPACING 3.5 MM; 9-POLE; 1,50 MM<sup>2</sup>; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 160; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 320; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 14 AWG;

Fine-stranded conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 14 AWG;

Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;

Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 1.5 mm<sup>2</sup>;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar poli: 9;

Numar total de conexiuni: 18;  
Total number of potentials: 9;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Note (conductor cross-section): Terminating 1.5 mm<sup>2</sup> conductors is possible; however insulation diameter does not allow clamping units to be terminated in a row.;  
Conductor entry direction to mating direction: 0; °  
Distanta intre pini: 3.5 mm / 0.138 inch;  
Latime: 43.3 mm / 1.705 inch;  
Inaltime: 18.5 mm / 0.728 inch;  
Adancime: 40.9 mm / 1.61 inch;  
Tip contact (pluggable connector): Distribution connectors;  
Connector (connection type): for conductors;  
Mismating protection: Yes;  
Locking of plug-in connection: locking lever;  
Culoare: light gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Copper alloy;  
Contact plating: tin-plated;  
Fire load: 0,343; MJ  
Greutate: 21,8; g  
Temperatura lucru: -60 ... +100 °C;  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4045454214609;  
Customs tariff number: 85366990990;  
Pret: 95,25 LEI (TVA inclus)

Detalii online: [https://www.materialelectrice.ro/2-conductor-combi-strip-100-protected-against-mismating-locking-lever-1-5-mm2-pin-spacing-3-5-mm-9-pole-1-50-mm2-light-gray-133962](https://www.materialeelectrice.ro/2-conductor-combi-strip-100-protected-against-mismating-locking-lever-1-5-mm2-pin-spacing-3-5-mm-9-pole-1-50-mm2-light-gray-133962)