



**WAGO FEEDTHROUGH TERMINAL BLOCK; PLATE THICKNESS: 1.5 MM; 2.5 MM²;
PIN SPACING 5.08 MM; 6-POLE; CAGE CLAMP®; 2,50 MM²; ORANGE**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 320; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 5; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 5; A

Tensiune nominala UL (Use Group C): 150; V

Curent nominal UL (Use Group C): 5; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 5; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 5; A

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm² / 28 ... 14 AWG;

Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm²;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 6;

Tehnologie conexiune 2: Wire-wrap pin;
Numar total de conexiuni: 6;
Total number of potentials: 6;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 5.08 mm / 0.2 inch;
Latime: 45.68 mm / 1.798 inch;
Inaltime: 14.3 mm / 0.563 inch;
Adancime: 15.5 mm / 0.61 inch;
Housing sheet thickness: 1.5 ... 1.5 mm / 0.059 ... 0.059 inch;
Tip montaj: Mounting flange;
Tip montaj: Feed-through mounting; Panel mounting;
Culoare: orange;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,163; MJ
Greutate: 9,7; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918270106;
Customs tariff number: 85366990990;
Pret: 58,76 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/feedthrough-terminal-block-plate-thickness-1-5-mm-2-5-mm2-pin-spacing-5-08-mm-6-pole-cage-clamp-2-50-mm2-orange-134306>