



**WAGO 4-LEVEL TERMINAL BLOCK FOR MATRIX PATCHING; FOR 35 X 15  
MOUNTING RAIL; 1,50 MM<sup>2</sup>; BLUE**

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 12; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;

Fine-stranded conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;

Strip length: 8 ... 10 mm / 0.31 ... 0.39 inch;

Numar total de conexiuni: 16;

Total number of potentials: 4;

Numar nivele: 4;

Wiring type: Front-entry wiring;

Latime: 7.62 mm / 0.3 inch;

Inaltime from upper-edge of DIN-rail: 62 mm / 2.441 inch;

Adancime: 126 mm / 4.961 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking: 0-1-2-3--3-2-1-0;

Marking level: Center marking;

Culoare: blue;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,597; MJ

Greutate: 33,9; g

Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4045454189730;  
Customs tariff number: 85369010000;  
Pret: 55,54 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-level-terminal-block-for-matrix-patching-for-35-x-15-mounting-rail-1-50-mm2-blue-134335>