



**WAGO THT MALE HEADER; 0.8 X 0.8 MM SOLDER PIN; ANGLED; PIN SPACING 3.5 MM; 12-POLE; BLACK**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 160; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 320; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 8; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 150; V

Curent nominal UL (Use Group B): 8; A

Certificari: UL 1059;

Numar poli: 12;

Total number of potentials: 12;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 3.5 mm / 0.138 inch;

Latime: 43.4 mm / 1.709 inch;

Inaltime: 10.3 mm / 0.406 inch;

Inaltime de la fata: 6.9 mm / 0.272 inch;

Adancime: 9.7 mm / 0.382 inch;

Lungimea pinului de contact: 3.4; mm

Solder pin dimensions: 0.8 x 0.8 mm;

Diametrul de gaurire cu toleranta: 1.2 (+0.1) mm;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for PCBs;

Mismating protection: No;  
Mating direction to the PCB: 0; °  
PCB contact: THT;  
Solder pin arrangement: over the entire male connector, in line;  
Number of solder pins per potential: 1;  
Culoare: black;  
Material group: I;  
Material izolator: Polyphthalamide (PPA GF);  
Flammability class per UL94: V0;  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,053; MJ  
Greutate: 2,6; g  
Temperatura lucru: -60 ... +100 °C;  
Product Group: 3 (Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454859688;  
Customs tariff number: 85366990990;  
Pret: 17,98 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-male-header-0-8-x-0-8-mm-solder-pin-angled-pin-spacing-3-5-mm-12-pole-black-134739>