



**WAGO 4-CONDUCTOR TERMINAL STRIP; SUITABLE FOR EX E II APPLICATIONS;  
9-POLE; WITHOUT PUSH-BUTTONS; WITH FIXING FLANGES; FOR SCREW OR  
SIMILAR MOUNTING TYPES; FIXING HOLE 3.2 MM Ø; 2.5 MM<sup>2</sup>; CAGE CLAMP®;  
2,50 MM<sup>2</sup>; LIGHT GRAY**

Tensiune nominala EN (Ex e II): 690; V  
Curent nominal (Ex e II): 23; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar poli: 9;  
Numar total de conexiuni: 36;  
Total number of potentials: 9;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Latime: 106 mm / 4.173 inch;  
Inaltime de la fata: 22.1 mm / 0.87 inch;  
Adancime: 32 mm / 1.26 inch;  
Module Latime: 10 mm / 0.394 inch;  
Design: horizontal;  
Marking level: Center marking;  
Culoare: light gray;  
Fire load: 1,073; MJ  
Greutate: 58,9; g

Product Group: 9 (Std. Chassis Mt. Blocks);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4044918415736;

Customs tariff number: 85369010000;

Pret: 63,36 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-terminal-strip-suitable-for-ex-e-ii-applications-9-pole-without-push-buttons-with-fixing-flanges-for-screw-or-similar-mounting-types-fixing-hole-3-2-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-light-gray-135770>