



**WAGO PCB TERMINAL BLOCK; 16 MM²; PIN SPACING 15 MM; 7-POLE; PUSH-IN
CAGE CLAMP®; 16,00 MM²; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 8; kV

Tensiune nominala (III/2): 1000; V

Tensiune nominala de supratensiune (III/2): 8; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 8; kV

Curent nominal: 76; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 1000; V

Tensiune nominala UL (Use Group C): 1000; V

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0,75 ... 16 mm² / 18 ... 4 AWG;

Fine-stranded conductor: 0,75 ... 25 mm² / 18 ... 4 AWG;

Fine-stranded conductor; with insulated ferrule: 0,75 ... 16 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0,75 ... 16 mm²;

Fine-stranded conductor; with twin ferrule: 0,75 ... 6 mm²;

Strip length: 18 ... 20 mm / 0.71 ... 0.79 inch;

Conductor connection direction to PCB: 0; °

Numar poli: 7;

Numar total de conexiuni: 7;

Total number of potentials: 7;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanța între pini: 15 mm / 0.591 inch;
Lățime: 101,6 mm / 4.000 inch;
Înălțime: 32,6 mm / 1.283 inch;
Înălțime de la față: 28,6 mm / 1.126 inch;
Adâncime: 29,1 mm / 1.146 inch;
Lungimea pinului de contact: 4; mm
Solder pin dimensions: 1,2 x 1 mm;
Diametrul de găurire cu toleranță: 1,7 (+0,1) mm;
Tip montaj: Feed-through mounting;
PCB contact: THT;
Solder pin arrangement: over the entire terminal strip (in-line);
Number of solder pins per potential: 6;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ESu);
Contact plating: tin-plated;
Greutate: 68,3; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Țara de origine: DE;
GTIN: 4055143861465;
Customs tariff number: 85369010000;
Preț: 108,75 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pcb-terminal-block-16-mm2-pin-spacing-15-mm-7-pole-push-in-cage-clamp-16-00-mm2-gray-135810>