



**WAGO DOUBLE-DECK TERMINAL BLOCK; GROUND CONDUCTOR/THROUGH  
TERMINAL BLOCK; PE/L; SUITABLE FOR EX E II APPLICATIONS; FOR DIN-RAIL 35  
X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; LIGHT GRAY**

Ratings per: IEC/EN 60947-7-1;  
Current nominal: 18; A  
Nominal voltage EN (Ex e II): 440; V  
Connection technology: CAGE CLAMP®;  
Operating tool:  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;  
Total number of connections: 4;  
Total number of potentials: 2;  
Number of levels: 2;  
Wiring type: Front-entry wiring;  
Width: 5 mm / 0.197 inch;  
Height from upper edge of DIN-rail: 40 mm / 1.575 inch;  
Depth: 70 mm / 2.756 inch;  
Design: horizontal;  
Mounting: DIN-35 rail;  
Potential marking: PE/L;  
Marking level: Side marking;  
Color: light gray;  
Weight: 13,9; g  
Packaging: BOX;  
Origin: DE;  
GTIN: 4045454323684;

Customs tariff number: 85369010000;  
Pret: 27,77 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-deck-terminal-block-ground-conductor-through-terminal-block-pe-l-suitable-for-ex-e-ii-applications-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-light-gray-136060>