



**WAGO TERMINAL STRIP; SUITABLE FOR EX I APPLICATIONS; 2-POLE; WITHOUT
PUSH-BUTTONS; WITH FIXING FLANGES M4; FOR SCREW OR SIMILAR
MOUNTING TYPES; FIXING HOLE 4.2 MM Ø; 2.5 MM²; CAGE CLAMP®; 2,50 MM²;
BLUE**

Tesiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar poli: 2;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 24.5 mm / 0.965 inch;

Inaltime de la fata: 27.6 mm / 1.087 inch;

Adancime: 33.4 mm / 1.315 inch;

Module Latime: 5 mm / 0.197 inch;

Design: horizontal;

Tip montaj: Mounting flange;

Marking level: Side marking;

Culoare: blue;

Fire load: 0,195; MJ
Greutate: 9,8; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821778530;
Customs tariff number: 85369010000;
Pret: 14,03 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/terminal-strip-suitable-for-ex-i-applications-2-pole-without-push-buttons-with-fixing-flanges-m4-for-screw-or-similar-mounting-types-fixing-hole-4-2-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-blue-136109>