



**WAGO TERMINAL STRIP; 4-POLE; WITHOUT PUSH-BUTTONS; WITH SNAP-IN MOUNTING FEET; FOR PLATE THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 + 0.1 MM Ø; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; LIGHT GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar poli: 4;

Numar total de conexiuni: 8;

Total number of potentials: 4;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 22.5 mm / 0.886 inch;

Inaltime de la fata: 27.6 mm / 1.087 inch;

Adancime: 33.4 mm / 1.315 inch;

Module Latime: 5 mm / 0.197 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: light gray;

Fire load: 0,337; MJ

Greutate: 17,9; g

Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918481434;  
Customs tariff number: 85369010000;  
Pret: 24,31 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/terminal-strip-4-pole-without-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-0-1-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-light-gray-136130>