



**WAGO PCB TERMINAL BLOCK; LEVER; 6 MM<sup>2</sup>; PIN SPACING 7.5 MM; 9-POLE;  
PUSH-IN CAGE CLAMP®; 6,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Tensiune nominala (III/2): 1000; V

Tensiune nominala de supratensiune (III/2): 8; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 8; kV

Curent nominal: 41; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 31; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 31; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Lever;

Solid conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG;

Fine-stranded conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 0,25 ... 6 mm<sup>2</sup>;

Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 6 mm<sup>2</sup>;

Fine-stranded conductor; with twin ferrule: 0,25 ... 2,5 mm<sup>2</sup>;

Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;

Conductor connection direction to PCB: 90; °

Numar poli: 9;

Numar total de conexiuni: 9;

Total number of potentials: 9;

Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Distanta intre pini: 7,5 mm / 0.295 inch;  
Latime: 70,35 mm / 2.77 inch;  
Inaltime: 31 mm / 1.22 inch;  
Inaltime de la fata: 27 mm / 1.063 inch;  
Adancime: 24 mm / 0.945 inch;  
Lungimea pinului de contact: 4; mm  
Solder pin dimensions: 1,5 x 1,2 mm;  
Diametrul de gaurire cu toleranta: 2 (+0,1) mm;  
PCB contact: THT;  
Solder pin arrangement: over the entire terminal strip (staggered);  
Number of solder pins per potential: 1;  
Culoare: gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Color of actuator: orange;  
Greutate: 38; g  
Temperatura lucru: -60 ... +105 °C;  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4055143586696;  
Customs tariff number: 85369010000;  
Pret: 68,38 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pcb-terminal-block-lever-6-mm2-pin-spacing-7-5-mm-9-pole-push-in-cage-clamp-6-00-mm2-gray-136185>