



Image coming soon

**WAGO 4-CONDUCTOR TERMINAL STRIP; 11-POLE; WITHOUT PUSH-BUTTONS;  
WITH SNAP-IN MOUNTING FEET; FOR PLATE THICKNESS 0.6 - 1.2 MM; FIXING  
HOLE 3.5 MM Ø; 1.5 MM<sup>2</sup>; CAGE CLAMP®; 1,50 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 18; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;

Fine-stranded conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar poli: 11;

Numar total de conexiuni: 44;

Total number of potentials: 11;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 92.4 mm / 3.638 inch;

Inaltime de la fata: 17 mm / 0.669 inch;

Adancime: 25 mm / 0.984 inch;

Module Latime: 8 mm / 0.315 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,504; MJ

Greutate: 30,2; g

Product Group: 9 (Std. Chassis Mt. Blocks);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4044918604604;

Customs tariff number: 85369010000;

Pret: 35,35 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-terminal-strip-11-pole-without-push-buttons-with-snap-in-mounting-feet-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-1-5-mm2-cage-clamp-1-50-mm2-gray-136218>