



**WAGO 2-CONDUCTOR PCB TERMINAL BLOCK; 1.5 MM²; PIN SPACING 5 MM; 5-
POLE; PUSH-IN CAGE CLAMP®; 1,50 MM²; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool;

Solid conductor: 0.2 ... 1.5 mm² / 24 ... 16 AWG;

Fine-stranded conductor: 0.2 ... 1.5 mm² / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0.25 ... 1 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 1 mm²;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Conductor connection direction to PCB: 45; °

Numar poli: 5;

Numar total de conexiuni: 10;

Total number of potentials: 5;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 5 mm / 0.197 inch;
Latime: 26.5 mm / 1.043 inch;
Inaltime: 23.3 mm / 0.917 inch;
Adancime: 19.8 mm / 0.78 inch;
Diametrul pinului de contact: 1; mm
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for PCBs;
Mating direction to the PCB: 90; °
PCB contact: THT;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy;
Contact plating: tin-plated;
Fire load: 0,131; MJ
Greutate: 6,5; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454077105;
Customs tariff number: 85369010000;
Pret: 12,60 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-pcb-terminal-block-1-5-mm2-pin-spacing-5-mm-5-pole-push-in-cage-clamp-1-50-mm2-gray-136320>