



**WAGO 2-CONDUCTOR PCB TERMINAL BLOCK; 0.75 MM<sup>2</sup>; PIN SPACING 7.5/7.62  
MM; 3-POLE; PUSH WIRE®; 0,75 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Tensiune nominala (III/2): 630; V

Tensiune nominala de supratensiune (III/2): 6; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 6; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Operating tool;

Solid conductor: 0.25 ... 0.75 mm<sup>2</sup> / 22 ... 18 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Conductor connection direction to PCB: 45; °

Numar poli: 3;

Numar total de conexiuni: 2;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Distanta intre pini: 7.5/7.62 mm / 0.295/0.3 inch;  
Latime: 24 mm / 0.945 inch;  
Inaltime: 20.5 mm / 0.807 inch;  
Inaltime de la fata: 16.5 mm / 0.65 inch;  
Adancime: 13.5 mm / 0.531 inch;  
Lungimea pinului de contact: 4; mm  
Solder pin dimensions: 0.5 x 0.75 mm;  
Diametrul de gaurire cu toleranta: 1.1 (+0.1) mm;  
PCB contact: THT;  
Solder pin arrangement: over the entire terminal strip, in line;  
Number of solder pins per potential: 2;  
Culoare: gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,087; MJ  
Greutate: 4,4; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918941648;  
Customs tariff number: 85369010000;  
Pret: 5,61 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-7-5-7-62-mm-3-pole-push-wire-0-75-mm2-gray-136914>