



WAGO PRE-ASSEMBLED ADAPTER CABLE; B2CA; SOCKET/PLUG MIDI; 3-POLE;
COD. S; 3 M; 1,50 MM²; BROWN

Note on Contact Resistance: approx. 1 m Ω of contact resistance approx. 0.25 m Ω contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Numar poli: 3;

Conductor preparation: tip-bonded;

Sheathed cable diameter: 7,4 ... 9,4 mm;

Sectiunea transversala a firului: 1,5; mm²

Connection type: RD socket - MIDI plug;

Retention force of a plug-in connection: when locked: > 80N;

Number of mating cycles: ?200, without resistive load 100, with resistive load $I_N = 20$ A, tested (2.5mm²/AWG 14);

Connection type: RD socket - MIDI plug;

Type of pre-assembled cable: Adapter cable;

Cable type: H05Z1Z1-F 3x1.5;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Application: Switching function;

Culoare: brown;

Material izolator: Polyamide 66 (PA 66);

Fire class per EN 50575: B2ca;

Contact material: Copper or copper alloy (surface-treated);

Fire load: 0,164; MJ

Strain relief Culoare: black;

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)

Insulating parts for temperatures ? 105 °C;

Tip ambalare: not packed;

Customs tariff number: 85444290900;

Pret: 92,50 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pre-assembled-adapter-cable-b2ca-socket-plug-midi-3-pole-cod-s-3-m-1-50-mm2-brown-137131>