



**WAGO STACKABLE 2-CONDUCTOR PCB TERMINAL BLOCK; 0.75 MM<sup>2</sup>; PIN SPACING 5/5.08 MM; 1-POLE; PUSH WIRE®; 0,75 MM<sup>2</sup>; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Operating tool;

Solid conductor: 0.25 ... 0.75 mm<sup>2</sup> / 24 ... 18 AWG;

Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 0.34 mm<sup>2</sup>;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Conductor connection direction to PCB: 0; °

Numar poli: 1;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;  
Distanta intre pini: 5/5.08 mm / 0.197/0.2 inch;  
Latime: 6.5 mm / 0.256 inch;  
Inaltime: 12.8 mm / 0.504 inch;  
Inaltime de la fata: 9.2 mm / 0.362 inch;  
Adancime: 12.5 mm / 0.492 inch;  
Lungimea pinului de contact: 3,6; mm  
Solder pin dimensions: 0.8 x 0.4 mm;  
Diametrul de gaurire cu toleranta: 1 (+0.1) mm;  
PCB contact: THT;  
Solder pin arrangement: within the terminal block, in line;  
Number of solder pins per potential: 2;  
Culoare: light gray;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,011; MJ  
Greutate: 0,7; g  
Temperatura lucru: -60 ... +105 °C;  
Product Group: 4 (Printed Circuit);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4044918831833;  
Customs tariff number: 85369010000;  
Pret: 1,43 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/stackable-2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-5-5-08-mm-1-pole-push-wire-0-75-mm2-light-gray-137372>