



**WAGO THR MALE HEADER; 1.2 X 1.2 MM SOLDER PIN; STRAIGHT; PIN SPACING  
7.5 MM; 11-POLE; BLACK**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Tensiune nominala (III/2): 630; V

Tensiune nominala de supratensiune (III/2): 6; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 15; A

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Numar poli: 11;

Total number of potentials: 11;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 7.5 mm / 0.295 inch;

Latime: 83 mm / 3.268 inch;

Inaltime: 14.4 mm / 0.567 inch;  
Inaltime de la fata: 12 mm / 0.472 inch;  
Adancime: 8.4 mm / 0.331 inch;  
Lungimea pinului de contact: 2,4; mm  
Solder pin dimensions: 1.2 x 1.2 mm;  
Diametru placat prin gaura (THR): 1.7 (+0.1) mm;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for PCBs;  
Mismating protection: No;  
Mating direction to the PCB: 90; °  
PCB contact: THR;  
Solder pin arrangement: over the entire male connector, in line;  
Number of solder pins per potential: 1;  
Culoare: black;  
Material group: I;  
Material izolator: Polyphthalamide (PPA GF);  
Flammability class per UL94: V0;  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,102; MJ  
Greutate: 4,5; g  
Temperatura lucru: -60 ... +100 °C;  
Product Group: 3 (Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4045454901097;  
Customs tariff number: 85366990990;  
Pret: 17,73 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/thr-male-header-1-2-x-1-2-mm-solder-pin-straight-pin-spacing-7-5-mm-11-pole-black-138784>