



**WAGO SOLDER PIN STRIP; 1.4 MM Ø SOLDER PIN; ANGLED; PIN SPACING 5 MM; 3-
POLE; BLACK**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Tensiune nominala (III/2): 630; V

Tensiune nominala de supratensiune (III/2): 6; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Numar poli: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 7.5 mm / 0.295 inch;

Latime: 25.7 mm / 1.012 inch;

Inaltime: 7.6 mm / 0.299 inch;

Inaltime de la fata: 4 mm / 0.157 inch;

Adancime: 12.3 mm / 0.484 inch;

Lungimea pinului de contact: 3,6; mm

Diametrul pinului de contact: 1,4; mm

Diametrul de gaurire cu toleranta: 1.6 (+0.1) mm;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for PCBs;

Mismating protection: No;

Mating direction to the PCB: 0; °

PCB contact: THT;

Culoare: black;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 0,8; g
Temperatura lucru: -60 ... +100 °C;
Tip ambalare: bag;
Tara de origine: CN;
GTIN: 4055143935470;
Customs tariff number: 85369010000;
Pret: 3,58 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/solder-pin-strip-1-4-mm-oe-solder-pin-angled-pin-spacing-5-mm-3-pole-black-139624>