



**WAGO THT FEMALE HEADER; 0.4 X 1.3 MM SOLDER PIN; ANGLED; PIN SPACING
7.5 MM; 3-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Tensiune nominala (III/2): 630; V

Tensiune nominala de supratensiune (III/2): 6; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Numar poli: 3;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 7,5 mm / 0.295 inch;

Latime: 20 mm / 0.787 inch;

Inaltime: 16 mm / 0.63 inch;

Inaltime de la fata: 13,6 mm / 0.535 inch;

Adancime: 15,4 mm / 0.606 inch;

Lungimea pinului de contact: 2,4; mm

Solder pin dimensions: 0,4 x 1,3 mm;

Diametru placat prin gaura (THR): 1,5 (+0,1) mm;

Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for PCB;
Mismating protection: No;
Mating direction to the PCB: 0; °
PCB contact: THR;
Culoare: light gray;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Contact material: Copper alloy;
Contact plating: tin-plated;
Fire load: 0,09; MJ
Greutate: 3,6; g
Temperatura lucru: -60 ... +100 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821396444;
Customs tariff number: 85366990990;
Pret: 13,44 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-female-header-0-4-x-1-3-mm-solder-pin-angled-pin-spacing-7-5-mm-3-pole-light-gray-139710>