



**WAGO SOLDER PIN STRIP; 1.4 MM Ø SOLDER PIN; ANGLED; PIN SPACING 5 MM; 8-POLE; BLACK**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Tensiune nominala (III/2): 320; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Tensiune nominala (II/2): 630; V  
Tensiune nominala de supratensiune (II/2): 4; kV  
Curent nominal: 16; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Numar poli: 8;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Distanta intre pini: 5 mm / 0.197 inch;  
Latime: 43.2 mm / 1.701 inch;  
Inaltime: 7.6 mm / 0.299 inch;  
Inaltime de la fata: 4 mm / 0.157 inch;  
Adancime: 12.3 mm / 0.484 inch;  
Lungimea pinului de contact: 3,6; mm  
Diametrul pinului de contact: 1,4; mm  
Diametrul de gaurire cu toleranta: 1.6 (+0.1) mm;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for PCBs;  
Mismating protection: No;  
Mating direction to the PCB: 0; °  
PCB contact: THT;

Culoare: black;  
Material group: I;  
Material izolator: Polyphthalamide (PPA GF);  
Flammability class per UL94: V0;  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Greutate: 2,2; g  
Temperatura lucru: -60 ... +100 °C;  
Tip ambalare: bag;  
Tara de origine: CN;  
GTIN: 4055143934558;  
Customs tariff number: 85369010000;  
Pret: 7,46 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/solder-pin-strip-1-4-mm-oe-solder-pin-angled-pin-spacing-5-mm-8-pole-black-139748>