



WAGO CONECTOR PENTRU ILUMINAT - CONEXIUNE 2-CONDUCTOR ; PUSH-BUTTON ON LIGHTING SIDE; LIGHTING SIDE: FOR ALL CONDUCTOR TYPES; 224 SERIES; MAX. 2.5 MM²; WHITE

Ratings per: EN 60664;

Tensiune nominala (II/2): 400; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 24; A

Legend (ratings): (II / 2) ? Overvoltage category II / Pollution degree 2;

Connection type (1): Installation side;

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Push-in;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 1 ... 2,5 mm² / 16 ... 14 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Connection type 2: Lighting side;

Tehnologie conexiune 2: CAGE CLAMP®;

Number of connection points: 1;

Solid conductor 2: 0,5 ... 2,5 mm² / 20 ... 14 AWG;

Fine-stranded conductor 2: 0,5 ... 2,5 mm² / 20 ... 16 AWG;

Numar total de conexiuni: 3;

Total number of potentials: 1;

Wiring type: Side-entry wiring;

Latime: 9,5 mm / 0.374 inch;

Inaltime: 15,5 mm / 0.61 inch;

Adancime: 20,5 mm / 0.807 inch;

Culoare: white;

Fire load: 0,046; MJ
Greutate: 2,1; g
Continuous operating temperature: 105 °C;
Product Group: 7 (Push Wire Conn.);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4044918583596;
Customs tariff number: 85369010000;

Pret: 0,96 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-lighting-connector-push-button-on-lighting-side-lighting-side-for-all-conductor-types-inst-side-for-solid-conductors-224-series-max-2-5-mm2-surrounding-air-temperature-max-600c-2-50-mm2-white-139870>