



**WAGO MULTILEVEL INSTALLATION TERMINAL BLOCK; 4 MM²; N/L/PE; PUSH-IN
CAGE CLAMP®; 2,50 MM²; GRAY**

Ratings (note): Potential – ground;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 32; A

Ratings (note) 2: Potential – potential;

Tensiune nominala (III/3) 2: 400; V

Tensiune nominala de supratensiune (III/3) 2: 6; kV

Curent nominal 2: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 5;

Total number of potentials: 3;

Numar nivele: 3;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 5,2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 42,3 mm / 1.665 inch;

Adancime: 96 mm / 3.78 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Potential marking: N/L/PE;

Marking level: Center/side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,245; MJ

Greutate: 16,3; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4044918925617;

Customs tariff number: 85369010000;

Pret: 15,23 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/multilevel-installation-terminal-block-4-mm2-n-l-pe-push-in-cage-clamp-2-50-mm2-gray-139883>