



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 35 MM²; WITH INTEGRATED
END PLATE; SIDE AND CENTER MARKING; ONLY FOR DIN 35 X 15 RAIL; CAGE
CLAMP®; 35,00 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 1000; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 125; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Nominal cross-section: 35 mm²;
Solid conductor: 6 ... 35 mm² / 8 ... 2 AWG;
Fine-stranded conductor: 6 ... 35 mm² / 8 ... 2 AWG;
Strip length: 23 mm / 0.91 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 16 mm / 0.63 inch;
Inaltime from upper-edge of DIN-rail: 53 mm / 2.087 inch;
Adancime: 100 mm / 3.937 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 1,078; MJ

Greutate: 87,3; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454218713;
Customs tariff number: 85369010000;
Pret: 51,48 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-35-mm2-with-integrated-end-plate-side-and-center-marking-only-for-din-35-x-15-rail-cage-clamp-35-00-mm2-gray-139989>