



WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM²; SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 2,50 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Curent nominal 2: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 20; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 20; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 20; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 20; A

Tensiune nominala EN (Ex e II): 550; V

Curent nominal (Ex e II): 22; A

Curent nominal (Ex e II) with jumper: 20; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;
Numar total de conexiuni: 3;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 5,2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 38,9 mm / 1.531 inch;
Adancime: 52,6 mm / 2.071 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,123; MJ
Greutate: 5,6; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4044918964920;
Customs tariff number: 85369010000;
Pret: 5,85 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-through-terminal-block-2-5-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-2-50-mm2-gray-140035>