



**WAGO 4-CONDUCTOR GROUND TERMINAL BLOCK; 1.5 MM<sup>2</sup>; SUITABLE FOR EX E  
II APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X  
7.5; PUSH-IN CAGE CLAMP®; 1,50 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 1,5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 2,5 mm<sup>2</sup> / 22 ... 14 AWG;

Solid conductor; push-in termination: 0,75 ... 2,5 mm<sup>2</sup> / 18 ... 14 AWG;

Fine-stranded conductor: 0,25 ... 2,5 mm<sup>2</sup> / 22 ... 14 AWG;

Fine-stranded conductor; with insulated ferrule: 0,75 ... 1,5 mm<sup>2</sup> / 18 ... 16 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0,75 ... 1,5 mm<sup>2</sup> / 18 ... 16 AWG;

Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 4,2 mm / 0.165 inch;

Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;

Adancime: 69,9 mm / 2.752 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: green-yellow;

Material izolator: Polyamide 66 (PA 66);

Greutate: 8,7; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4055143616973;

Customs tariff number: 85369010000;

Pret: 20,48 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-ground-terminal-block-1-5-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-1-50-mm2-green-yellow-140054>