



**WAGO SOCKET; WITH AUTOMATIC CUTTING OF LIVE CONDUCTOR; 3-POLE;  
ORANGE**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Tensiune nominala (III/2): 630; V  
Tensiune nominala de supratensiune (III/2): 6; kV  
Tensiune nominala (II/2): 1000; V  
Tensiune nominala de supratensiune (II/2): 6; kV  
Curent nominal: 10; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group C): 600; V  
Curent nominal UL (Use Group C): 10; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group C): 600; V  
Curent nominal CSA (Use Group C): 10; A  
Tehnologie conexiune: IDC;  
Fine-stranded conductor: 0,75 ... 1,5 mm<sup>2</sup> / 18 ... 16 AWG;  
Numar poli: 3;  
Total number of potentials: 3;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Latime: 26,5 mm / 1.043 inch;  
Inaltime: 27 mm / 1.063 inch;  
Adancime: 23 mm / 0.906 inch;  
Tip contact (pluggable connector): Conector mama/priza;  
Connector (connection type): for conductor;  
Culoare: orange;

Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Brass;  
Contact plating: tin-plated;  
Fire load: 0,169; MJ  
Greutate: 7,1; g  
Temperatura lucru: -60 ... +85 °C;  
Product Group: 13 (Misc. Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4050821429715;  
Customs tariff number: 85366990990;  
Pret: 15,77 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/socket-with-automatic-cutting-of-live-conductor-3-pole-orange-140101>