



WAGO H-DISTRIBUTION CONNECTOR; 5-POLE; COD. I; 1 INPUT; 2 OUTPUTS; OUTPUTS ON BOTH SIDES; 3 LOCKING LEVERS; FOR FLYING LEADS; BLUE

Note on Contact Resistance: approx. 1 m Ω of contact resistance approx. 0.25 m Ω contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensione nominale (III/3): 400; V

Tensione nominale de supratensione (III/3): 6; kV

Curent nominal: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensione nominale UL 1977: 600; V

Curent nominal UL 1977: 23; A

Numar poli: 5;

Total number of potentials: 5;

Ground function: with preceding ground contact;

Distanza intre pini: 10 mm / 0.394 inch;

Latime: 50 mm / 1.969 inch;

Inaltime: 36,7 mm / 1.445 inch;

Adancime: 46 mm / 1.811 inch;

Technologie: DALI;

Coding: I;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: ?200, without resistive load 100, with resistive load $I_N = 25$ A, tested (4 mm²/AWG 12);

Distributor type: h-distribution connector (bi-directional);

Marking: N ? L DA- DA+;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Potential marking: N ? L DA- DA+;

Application: Lighting management;

Suitable: for flying leads;

Tip contact (pluggable connector): Socket/plug;

Mismatching protection: Yes;

Locking of plug-in connection: locking lever;

Locking lever: yes;

Number of locking levers: 3;

Culoare: blue;

Material izolator: Polyamide 66 (PA 66);

Contact material: Copper or copper alloy (surface-treated);

Fire load: 0,638; MJ

Greutate: 38,4; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;

Product Group: 20 (WINSTA);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454853433;

Customs tariff number: 85366990990;

Pret: 69,09 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/h-distribution-connector-5-pole-cod-i-1-input-2-outputs-outputs-on-both-sides-3-locking-levers-for-flying-leads-blue-140138>