



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM²; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 2,50 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 27,5 mm / 1.083 inch;

Adancime: 44,5 mm / 1.752 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,08; MJ

Greutate: 4,3; g

Product Group: 16 (Rail Mounted Terminal Block with CCC);

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918478250;
Customs tariff number: 85369010000;
Pret: 4,42 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-2-5-mm2-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-2-50-mm2-gray-140153>