



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 6 MM²; CENTER MARKING;
FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 6,00 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 41; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Fine-stranded conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 8 mm / 0.315 inch;

Inaltime from upper-edge of DIN-rail: 32,5 mm / 1.28 inch;

Adancime: 74,5 mm / 2.933 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,267; MJ

Greutate: 15,8; g

Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4044918445801;
Customs tariff number: 85369010000;
Pret: 10,39 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-6-mm2-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-6-00-mm2-gray-140169>