



### **WAGO SOCKET; 6-POLE; GRAY**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Tensiune nominala (III/2): 630; V  
Tensiune nominala de supratensiune (III/2): 6; kV  
Tensiune nominala (II/2): 1000; V  
Tensiune nominala de supratensiune (II/2): 6; kV  
Curent nominal: 10; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Tensiune nominala UL (Use Group C): 600; V  
Curent nominal UL (Use Group C): 10; A  
Certificari: UL 1059;  
Tensiune nominala CSA (Use Group C): 600; V  
Curent nominal CSA (Use Group C): 10; A  
Tehnologie conexiune: IDC;  
Fine-stranded conductor: 0,75 ... 1,5 mm<sup>2</sup> / 18 ... 16 AWG;  
Numar poli: 6;  
Total number of potentials: 6;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Latime: 43 mm / 1.693 inch;  
Inaltime: 16 mm / 0.63 inch;  
Adancime: 30 mm / 1.181 inch;  
Tip contact (pluggable connector): Conector mama/priza;  
Connector (connection type): for conductor;  
Culoare: gray;  
Material group: I;

Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Brass;  
Contact plating: tin-plated;  
Fire load: 0,273; MJ  
Greutate: 12,3; g  
Temperatura lucru: -60 ... +85 °C;  
Product Group: 13 (Misc. Multi Conn. System);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918253444;  
Customs tariff number: 85366990990;  
Pret: 13,50 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/socket-6-pole-gray-140259>