



**WAGO 2-CONDUCTOR/1-PIN CARRIER TERMINAL BLOCK; FOR DIN-RAIL 35 X 15  
AND 35 X 7.5; 2.5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®; 2,50 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 690; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Curent nominal 2: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Number of connection points (connection type): 2;

Tip actionare: Open Tool Slot; Push-in;

Connectable conductor materials: Copper;

Nominal cross-section: 2.5 mm<sup>2</sup>;

Solid conductor: 0.25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0.75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0.25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2.5 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2.5 mm<sup>2</sup> / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Number of connection points: 1;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Latime: 5.2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 32.5 mm / 1.28 inch;

Adancime: 59.2 mm / 2.331 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,136; MJ  
Greutate: 6,3; g  
Product Group: 18 (X-COM-System);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4050821145127;  
Customs tariff number: 85366990990;  
Pret: 7,76 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-1-pin-carrier-terminal-block-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-140318>